# **OPERATING INSTRUCTIONS**

7 DAY HEAVY-DUTY DUAL OUTLET TIMER FD60-U6

# **PRODUCT**



### Heating systems · Indoor sprinklers

Lighting

- **WARNING**
- Electrical shock hazard

Humidifiers

Nebulizers

· Risk of fire · For indoor use only

Aquariums

Ventilators

- A. INITIAL SETUP
- · Risk of injury or death Use a grounded outlet

remove sticker from face of screen.

30 minutes to charge the internal battery.

Cooling systems

- · Follow local electrical codes

88:88:88

## 1. Remove sticker

## 2. Charge the internal battery If the screen is blank, plug the timer into any outlet for

3. Reset the timer

Press the "RESET" button with the tip of a small non-metallic insulated tool, such as a pencil or

toothpick. LCD display will appear like this icon.

Locate the tab at the top right of the sticker and pull to


## 4. Unplug and program timer


Charging the battery allows the programming and setup of timer to occur from the comfort of your chair! **B.** SET UP CURRENT DAY & TIME



## WEEK HOUR MIN R LOCK PROG ON/AUTO/OF

12:0000.





9:00<sub>00</sub> .

WFFK HOUR MIN R



Fig 05

want.

SA, SU MO to SA

Day combination options: MO to SU Individual day: MO,TU,WE,TH,FR,SA,SU MO to FR

Note: Press "WEEK" mutiple times until you get the day combination you

3. Press the "HOUR" button until 8:00am displays on the ON screen. (Fig 06) Fig 06




Fig 08

Fig 09

PM

8:88

Press "R" at any point to cancel the current setting. Press "R" again will take you back to the previous option.

6. Repeat steps 2 to 4 to set program "1 OFF". (Fig 09)

5. Press the "**PROG**" button once to set program

"1 OFF" you will see the picture. (Fig 08)

timer.

Pressing ON/AUTO/OFF button can manually turn on and off the timer.

7. If you want to set the second ON/OFF program, press "PROG" button

Plug the devices into the outlets on either side of the

8:8800

8:8000

9:80<sub>00</sub>

8:8000

Fig 12

MANUAL OVERRIDE

 OFF: Press ON/AUTO/OFF button until screen shows OFF. In this status, timer always has no output. The red

LED output indicator on the top is off. (Fig10)

the programs as previously set. (Fig12)

run the programs as previously set. (Fig13)

Attach up to TWO DEVICES to the timer

Please set timer to AUTO status if you want to turn on and off automatically based on Programs you have set. There are two AUTO status: AUTO ON: Press ON/AUTO/OFF button to the ON first, then press to the AUTO. It is ON status of the timer, top red LED indicator is ON, the timer will run



the previously programmed ON and OFF times will be separately postponed by 2-32 minutes. (Fig 14) Press the "WEEK" and "HOUR" buttons again to turn off the Random function.

# Press HOUR & MIN simultaneously to activate or deactivate DST Note: A small clock symbol "O" will appear on the far right of the LCD screen

### (Fig 15) DST OFF (Fig 17) DST OFF (Fig 16) DST ON

Otherwise it returns to current time. (Fig 17)

It means manually add 1hour to open the "Summer Time",

when DST is active. (Fig 16)

**G**. TROUBLESHOOTING

settings.

Timer does not turn on or off.


b. Timer program should be on AUTO setting.


be set by different programs. f. If the timer can not Turn ON or Turn OFF on time, please check if the

Customer Service Asstiance: 1-909-592-1881

Email: Support@centurytimer.com Business Hours of Operation: 9AM to 5PM Pacific time, Monday to Friday Manufactured and Distributed by: Century Products Inc. www.centurytimer.com

Random function is in deactive status. g. If the timer always ON or always OFF, please check if the program is in Auto mode. H. TECHNICAL DATA Rated Voltage: 115VAC, 60Hz Max.Load: 15A, 1725W





MO, WE, FR TU, TH, SA MO, TU, WE TH, FR, SA

screen. (Fig 07)

again, you can repeat steps 2 to 6 to set program, or press the "CLOCK" to return the current time. You can set up to 8 different ON and OFF programs for your timer. To do so, just repeat steps 1 to 6 for program "2 ON" "2 OFF" "3 ON" etc. . . 8. If you want to make the set of programs valid, please press "ON/AUTO/OFF" button to make sure the timer is in AUTO mode.

• ON: Press ON/AUTO/OFF button until screen shows ON. In this status, timer always has output. The red LED output indicator on the top is on. (Fig11)

 AUTO OFF: Press ON/AUTO/OFF button to the OFF first, then press to the AUTO. It is OFF status of the timer, top red LED indicator is OFF, then the timer will

security mode. "O" is to the right side of the display. When the timer is working in Auto mode and the random function is on, DST - DAYLIGHT SAVING TIME FUNCTION

c. Make certain that both an ON and OFF time have been specified. d. If the number is not clear or blank on the screen, please plug the timer into any outlet for 30 minutes to charge the internal battery, then press the Reset button. e. The 2 grounded outlets are controlled by the same programs, they can not

a. Make sure AM and PM are correct on the current time and in the program